

## GENERAL NOTES


The maximum spacing between channelizing devices in a taper should be 12m; the maximum spacing between channelizing devices used to separate traffic should be 25m.

Channelizing devices shall be a minimum of 0.7m in height.

Traffic safety drums shall be used for channelization devices during nighttime operations. (See Special Provisions)

## LEGEND

- ▣ ▣ ▣ CHANNELIZING DEVICES
- ◼ SIGN
- ◄◄ SEQUENTIAL ARROW SIGN

DESIGNED BY B. McMULLEN				REGION NO. 10	STATE WASH	FED.AID PROJ.NO. 1M-0051(236)	ENVIRONMENTAL AND ENGINEERING SERVICE CENTER	 <b>Washington State</b> Department of Transportation	SR 5 NEWAUKUM RIVER BRIDGE TO THURSTON COUNTY LINE	REFERENCE SHEET NUMBER
ENTERED BY W. CASEY				JOB NUMBER 96X329						SHEET 13 OF 13 SHEETS
CHECKED BY D. HOKANSON				CONTRACT NO.						
PROJ. ENGR. T. PASELK										
DIST. ADM. G. E. SMITH	DATE	DATE	REVISION	BY				as\dgn\127381r.f.dgn	31 JAN 97	TRAFFIC CONTROL PLAN